



DESSILLONS & DUTRILLAUX - Since 1949

# TECHNICAL CHARACTERISTICS

CT 041

Pneumatic tourniquet G10903 Easy Pump dual 2 tubes

Index 2

**MADE IN FRANCE** 

## Regulatory information

CE Marking	Index of classification	Notified body	<del>PHTHALATES LATEX</del>
CE 0120	Ila	SGS	



**Dessillons & Dutrillaux**  
**Zone Industrielle La Tuque - 47240 CASTELCULIER**  
 Tél : +33 5 53 48 30 66 Fax : +33 5 53 47 24 64  
 technique@ddmedical.fr www.ddmedical.fr



**Technical characteristics Easy Pump G10903**

STORAGE CONDITIONS		T : -5° à 40°C, Humidity : 20- 80 %
CONDITIONS OF USE		T : 5° à 40°C, Humidity : 20 – 80 % Maximum altitude 2000 m
CASE MATERIALS	Density Shock resistance UL flammability test Heat stability Hardness	ABS (Acrylonitrile Butadiene Styrene) 1.112 g/ cm <sup>3</sup> > 25 KJ / m <sup>2</sup> UL94 V-0 85°C 78
DIMENSIONS		CASE
	Height (mm)	250
	Width (mm)	300
	Depth (mm)	190
	Width (mm)	SCREEN
	Height (mm)	120
		90
WEIGHT kg		4.2 KGS
LINE VOLTAGE		100 - 240 V AC
LINE FREQUENCY		50 – 60 Hz
POWER PLUG		60 VA
FUSE		
Input power card		F2AH/250V
Output power card		F1,6AH/15V
Battery		F8AH/12V
PULSED POWER SUPPLY		Entry : 90-264 Vac, 47-63 Hz, 1.8 – 1 A Exit : 15 Vdc, 4A
BATTERY		Rechargeable
	Type	Pb
	Voltage	12 Volts
	Ampere	4000 mAh
	Charging time	8 h
	Autonomy	10 h
PUMP		
	Type	Membrane pump
	Pump flow	4.6 l/mn
PRESSION		
	Type	1.7 bar
	Service	0 to 600 mmHg
	Setting range	± 1 mm Hg
	Setting precision	± 5 mm Hg
	Display accuracy	
	Alarm	An audible and visual alarm
	Number of independant pressure circuit	2
TIMER		
	Units	minutes
	Alarm	Programmable audible and visual alarm
CONNECTION		
	Pneumatic	2 female coupler CPC type



DESSILLONS & DUTRILLAUX - Since 1949

## TECHNICAL CHARACTERISTICS

CT 041

Pneumatic tourniquet G10903 Easy Pump dual 2 tubes

Index 2

Electric	Connector CEE22
MAXIMUM SOUND LEVEL WHILE FUNCTIONING	52 dB

**Dessillons & Dutrillaux**  
**Zone Industrielle La Tuque - 47240 CASTELCULIER**  
**Tél : +33 5 53 48 30 66 Fax : +33 5 53 47 24 64**  
**technique@ddmedical.fr www.ddmedical.fr**

Certified ISO 13485



Page 3 / 3